BAYRO® SUPER TEC 20W 50

High-performance universal engine oil

PROPERTIES

BAYRO SUPER TEC 20W 50 is a mineral high-performance universal engine oil of viscosity class SAE 20W-50. Base oils produced with the latest refinery technology and carefully selected innovative additives guarantee that the product meets the highest requirements. Among its most outstanding properties are the excellent shear stability at high temperatures and exceptional wear protection under all operating conditions. Cleaning additives prevent deposits, keep pistons and valves clean and protect the engine against black sludge. Clean engines and low friction reduce energy loss in the engine and minimise servicing costs..

USE INSTRUCTIONS

BAYRO SUPER TEC 20W 50 is a high-performance engine oil for universal use, even under heavy-duty conditions. It is recommended for passenger car petrol and diesel engines with or without turbocharging. It meets the stringent requirements of modern fuel-efficient engines and the latest emissions standards with a generous safety margin.

PERFORMANCE DATA

Specifications:

- ACEA A3/B4
- API SL/CF

TYPICAL VALUES	METHOD	UNIT	BAYRO SUPER TEC 20W 50
Dichte bei 15°C Viskosität	DIN 51 757	kg/m³	888
bei 40°CViskosität bei	DIN 51 562	mm²/s	164
100°CViskositätsindex (VI)	DIN 51 562	mm²/s	17.6
Viskosität bei -15°C	DIN ISO 2909	-	120
Pourpoint Flammpunkt	DIN 51 377	mPa.s	8190
COC	DIN ISO 3016	°C	-24
TBN	DIN ISO 2592	°C	238
	DIN ISO 3771	mg KOH/g	10,7

* entspricht den Anforderungen des OEM-Herstellers.
Die angegebenen Werte können im handelsüblichen Rahmen schwanken.

BAYEROL MH GmbH
Trimburgerstr. 2 • D-81249 München • info@bayerol.de
www.bayerol.de